

# UHU® DRY & CLEAN ROLLER PERMANENT REFILL

## GLUE ROLLER PERMANENT REFILL UNIT



**Stains/residue:** UHU DRY & CLEAN ROLLER can be easily washed out with cold water.

### TECHNICAL SPECIFICATIONS

**Appearance:** Colourless

**Chemical base:** Water-based acrylate adhesive

**pH-value:** approx. 7

### STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

### PHYSIOLOGICAL PROPERTIES

UHU DRY & CLEAN ROLLER is physiologically safe.

### PACK SIZES

UHU DRY & CLEAN ROLLER permanent is available with a tape length of 14m and width of 8.4mm as reusable roller and exchangeable unit in folding box.

### PRODUCT DESCRIPTION

The eco-friendly refill unit for permanent, clean and precise glueing of paper, cardboard and photos to similar materials and many smooth surfaces. Glues immediately, needs no drying time and is solvent free. The tape length is 14.0 m, the tape width is 8.4 mm. The packaging is made of more than 85% recycled cardboard.

### FIELD OF APPLICATION

Suitable for permanent glueing of paper, cardboard and photos to similar materials and many other smooth surfaces.

### PROPERTIES

- Permanent, clean and precise
- Instant glueing - no drying time
- Without solvents
- Tape 14.0 m x 8.4 mm
- Packaging >85% recycled cardboard

### PREPARATION

**Surface requirements:** Materials to be glued must be clean, dry and free from dust and grease.

### APPLICATION

#### Directions for use:

Open the integrated cap, position the roller on the material you want to glue and pull it back while you press down. The glue is applied with gentle pressure and the soft, extra wide waltz ensures an even contact pressure and therefore a better application. Then immediately put together press the two parts to be glued. A loose tape can be retightened by adjusting the tape tightening screw.

Note: This information is the result of carefully executed tests. This Technical Data Sheet has been prepared to the best of our knowledge to provide you with advice when glueing. We cannot be held responsible for the results or any damage suffered, as the variety of factors involved (type and combination of materials and working method) are beyond our control. Users have to carry out their own checks and trials. Liability can only be accepted for the consistently high quality of our product.