

UHU® HOT MELT GLUE STICKS TRANSPARENT

TRANSPARENT, HIGH-STRENGTH, 11MM DIAMETER



PREPARATION

Surface requirements: The surface must be dry, clean and free of dust and grease.

APPLICATION

Directions for use:

Apply the glue quickly, and not too sparingly. Stick the two pieces together immediately. Always apply the glue to the harder material. Glue application: on flexible surfaces, apply the glue in thick lines; on hard surfaces, you can apply the glue in thick lines or in dots. The glue can be used to fill small holes and cracks.

Stains/residue: Cured adhesive residue can only be removed mechanically.

Points of attention: Do not use at temperatures below +5°C. Never remove glue sticks from glue gun, this could damage the mechanism.

PACK SIZES

UHU Hot Melt GLUE STICKS 200 g, 500 g, 10 kg

PRODUCT DESCRIPTION

Transparent and high-strength HOT MELT glue sticks Folding Box with a diameter of 11 mm for DIY work, repairing, fixing, sealing and insulating. Ideal usable/workable in UHU GLUE GUNS STARTER KIT/PROMATIC HOT MELT, but also suited for all commercially available hot melt glue guns with Ø 11mm glue sticks. For glueing heat-sensitive materials we recommend using the UHU glue gun Creative/ Creative XL LOW MELT 110°C.

FIELD OF APPLICATION

Glues many porous and non porous materials in seconds such as wood, metal, stone, glass, tiles, ceramic, leather, textiles and many plastics. With a high melting capacity and is suited for DIY and all household repairs. Glues almost all materials quickly, neatly, permanently and reliably. Ideal for fixing, repairing, isolating and sealing. For example carpets, shoe soles and heels, mounting laths, skirting boards or glueing a loose tile. Multifunctional. Especially for do-it-yourself and semi-professional use. Not suitable for PE, PP, PTFE, as well as heat sensitive materials. Supporting elements or objects permanently under tension.

PROPERTIES

- Transparent and high-strength
- Short setting time
- Weather resistant
- Temperature resistant up to +70°C
- Does not shrink, does not age
- Solvent-free
- Resistant to UV-light, washing powders and detergents
- Good electrical insulating capacity
- Crack filling
- Ø 11 mm

Note: This information is the result of carefully executed tests. This Technical Data Sheet has been prepared to the best of our knowledge to provide you with advice when gluing. We cannot be held responsible for the results or any damage suffered, as the variety of factors involved (type and combination of materials and working method) are beyond our control. Users have to carry out their own checks and trials. Liability can only be accepted for the consistently high quality of our product.