

UHU[®] STIC MAGIC

BLUE GLUE STICK SOLVENT FREE WITH DISAPPEARING COLOR



Stains/residue: UHU stic Magic Blue can be easily washed out with cold water.

CURE TIMES*

Drying/Curing time: approx. 60 seconds

Final bonding strength after: approx. 60 seconds

* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

TECHNICAL SPECIFICATIONS

Appearance: Blue wax-like mass, dries transparent

Chemical base: Polyvinyl Pyrrolidone

Colour: Blue (transparent)

Consistency: Solid, but easy to apply

Solvent: Water

pH-value: approx. 11,5

STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

PHYSIOLOGICAL PROPERTIES

UHU stic Magic Blue is physiologically safe.

PACK SIZES

glue stick: 8.2g, 21g, 40g in tray or on blistercard

PRODUCT DESCRIPTION

Blue glue stick "Made in Germany" where You can directly see where the glue is applied. Applies blue and magically dries clear. With an unique screw cap that prevents glue from drying out. The glue formula consists of 98% natural ingredients (including water) and is solvent free. Glues strong, fast and durable, glides smoothly, is highly efficient and of course cold washable.

FIELD OF APPLICATION

Suitable for glueing paper, cardboard, photos, Styrofoam[®] (expanded polystyrene), labels, textiles, etc. Ideal for use at home, office, school and Kindergarten

PROPERTIES

- Applies blue and magically dries clear
- Unique screw cap that prevents glue from drying out
- Solvent free glue formula with 98% natural ingredients (including water)
- Glues fast, strong and durable
- Very good direct tack
- Highly efficient
- Glides smoothly and cold washable

PREPARATION

Surface requirements: Materials to be glued must be clean, dry and free from dust and grease. One of both surfaces must be absorbent.

APPLICATION

Directions for use:

UHU stic Magic Blue is applied with light pressure onto the materials to be glued. The parts are put together immediately after applying the glue. The blue color disappears a few seconds after application and it is transparent when dry.

Note: This information is the result of carefully executed tests. This Technical Data Sheet has been prepared to the best of our knowledge to provide you with advice when gluing. We cannot be held responsible for the results or any damage suffered, as the variety of factors involved (type and combination of materials and working method) are beyond our control. Users have to carry out their own checks and trials. Liability can only be accepted for the consistently high quality of our product.