

UHU® ALL PURPOSE ADHESIVE SUPER

SUPER STRONG AND SUPER FAST ALL PURPOSE ADHESIVE



PRODUCT DESCRIPTION

UHU All Purpose Adhesive SUPER bonds super strong and super fast - but remains adjustable for approx. 20 seconds and does not stick fingers together immediately. The patented formula is suitable for virtually all flexible, solid, porous and non-porous materials. Withstands vibrations and shocks, is flexible, transparent and odourless. Humidity and temperature resistant from -50°C to +100°C.

FIELD OF APPLICATION

Universal - glues porcelain, ceramic, many plastic materials, metal, wood, glass, leather, rubber, Styrofoam®, paper, cardboard, and much more. Not suitable for leather clothing, textiles, Polythylene (PE) and Polypropylene (PP).

PROPERTIES

- super strong
- super fast
- adjustable - no immediate finger bonding
- patented formula

PREPARATION

Surface requirements: Materials to be glued must be clean, dry and free of dust and grease.

APPLICATION

Directions for use:

Surfaces to be glued together must be dry and free of dust and grease. Apply a thin layer of adhesive to one side. Press parts together. Glue joint remains adjustable for approx. 20 seconds. Surfaces to be glued together must be of exactly the same shape and size.

Stains/residue: Remove wet glue stains immediately with acetone. Hardened glue can only be removed mechanically.

Advice: The thinner the glue layer, the faster and stronger the final bond.

Points of attention: Contains cyanoacrylate. Bonds skin and eyelids together in seconds. If product comes into contact with the eyes, rinse immediately with plenty of water and seek medical advice. In case of contact with skin, glue can be dissolved by soaking in warm soapy water. Then apply skin cream. Keep out of the reach of children.

CURE TIMES*

Drying/Curing time: approx. The bond remains repositionable within 20 and 60 seconds, which means that fingers don't get stuck immediately.

Depending on the materials, UHU All Purpose Adhesive Super Strong & Safe forms a strong, reliable bond in 20 seconds to a few minutes.

Final bonding strength after: approx. After 24 hours the adhesive joint can be fully stressed.

* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

TECHNICAL PROPERTIES

Temperature resistance: Joins are resistant and temperature (-50°C up to +100°C) for short periods.

TECHNICAL SPECIFICATIONS

Appearance: colourless, clear

Chemical base: UHU development - partly consisting of cyanoacrylate

Consistency: Gel

STORAGE CONDITIONS

Store in a dry, cool and frost-free place.