

# UHU® CORRECTION PEN

## LIQUID CORRECTION PEN FOR FAST, CLEAN AND PRECISE CORRECTION



### TECHNICAL SPECIFICATIONS

**Appearance:** white fluid

**Chemical base:** acrylate resin with titanium dioxide

**Solid matter:** approx. 54 %

**Density:** approx. 0,97 g/cm<sup>3</sup>

### STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

### PACK SIZES

UHU CORRECTION PEN is available as 2x5ml on blistercard and as 8ml in tray or on blistercard.

### PRODUCT DESCRIPTION

Liquid correction pen for fast and precise correction of printed or handwritten text and small areas such as dots and lines. With a special metal tip for extra precise and smooth application. The pen is soft and very easy to squeeze. The fluid dries fast and has a high covering power. Suitable on all common types of paper (except thermal paper). The packaging is made of more than 85% recycled cardboard.

### FIELD OF APPLICATION

Suitable for printed or handwritten texts on every type of paper (except thermal paper) Not suitable for thermal paper.

### PROPERTIES

- For correction of dots, fine lines and small areas
- Soft pen - easy to squeeze
- Metal tip for precise and smooth application
- Fast drying, with high covering power
- Suitable for all kinds of paper (ex. thermal paper)

### APPLICATION

#### Directions for use:

Shake pen until you hear the mixing ball inside. Before first use, remove the protection cover from the metal tip. Shake the pen until you hear the mixing ball inside. Press gently with the pen to apply correction fluid to the required area. The metal tip allows you to control the amount dispensed precisely and economically. Leave to dry for a few moments before writing on the corrected area. Replace cap on pen immediately after use.

**Stains/residue:** Correction fluid can be removed from smooth surfaces, when dry, preferably with mechanical action using a blade or spatula.

Note: This information is the result of carefully executed tests. This Technical Data Sheet has been prepared to the best of our knowledge to provide you with advice when gluing. We cannot be held responsible for the results or any damage suffered, as the variety of factors involved (type and combination of materials and working method) are beyond our control. Users have to carry out their own checks and trials. Liability can only be accepted for the consistently high quality of our product.