



# CORRECTION SIDEWAY ROLLER

## ERGONOMIC SIDEWAY APPLICATION



### PRODUCT DESCRIPTION

Ergonomic Correction Roller Sideway. The ergonomic correction roller for clean and precise correction of printed and handwritten texts on almost all types of paper. Can be written on immediately, no drying time and solvent free. With innovative tape guidance system for easy and convenient sideway application. The tape length is 8.0m, the tape width is 5.0mm. The roller (housing) consists of 100 % recycled plastic and the packaging is made of more than 85 % recycled cardboard.

### FIELD OF APPLICATION

For printed or handwritten texts on almost all types of paper.

### PROPERTIES

- Ergonomic sideway application
- For fast and precise correction of printed or handwritten texts
- Can be written on immediately – no drying time
- Suitable for all types of paper
- Solvent free
- Roller (housing): 100 % recycled plastic
- Tape 8.0m x 5.0mm
- Packaging >85 % recycled cardboard

### APPLICATION

#### Directions for use:

Place the roller on the position you want to correct and pull it sideways while you press down gently. Can be written on immediately. A loose tape can be retightened by adjusting the tape tightening screw. Close protection cap after use. Can be used at almost any angle, making it also ideal for left-handed people to use.

**Stains/residue:** Correction tape can be removed from smooth surfaces, when dry, preferably with mechanical action using a blade or spatula.

### TECHNICAL SPECIFICATIONS

|                |                                      |
|----------------|--------------------------------------|
| Chemical base: | Acrylate resin with titanium dioxide |
| Colour:        | White                                |
| Consistency:   | Solid                                |
| Paintability:  | Yes                                  |
| Solvent free:  | Yes                                  |

### PACK SIZES

Available as single-use roller 8m x 5mm on blistercard or in folding box.

### STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.