

UHU®

CREATIV FABRICS, FELT & RIBBONS

FLEXIBLE, RESISTANT TO WASHING AND DRY-CLEANING

PRODUCT DESCRIPTION

UHU Creativ Fabrics, Felt & Ribbons is fast-setting, solvent-free, resistant to washing and dry-cleaning (if ironed), odourless and transparent when dry. The gluing film is very flexible and resistant to ageing and light – the ideal adhesive for making dolls, fabric animals, puppets, silk flowers, clothing, bags, greeting cards, book bindings, table and room decorations, collages, ribbon ornaments and much more.

FIELD OF APPLICATION

Glues fabric, felt and ribbons, also in conjunction with many other materials. Also for wool, wadding, pompoms, pipe cleaners, cord, etc.

Not suitable for silk and fabrics with an over 60% share of synthetics.

PROPERTIES

- Resistant to washing and dry-cleaning
- Flexible
- Resistant to ageing and light
- Odourless and transparent when dry
- Fast-setting
- Solvent-free

PREPARATION

Surface Requirements: The areas to be glued must be dry and free of any dust or grease.

APPLICATION

Directions for use:

A brush or spatula may be used to apply the glue. In most cases it is sufficient to apply the glue to one side only. The parts may be assembled either immediately or after no more than approx. 5 minutes drying time. After approx. 30 minutes, the assembly can be ironed (iron setting according to the type of fabric), this shortens the bonding time and improves resistance to washing and cleaning.

Stains/residue: Fresh specks of glue may be removed with water. Dried-on glue is extremely hard to remove because of the good resistance of the product to solvents and cleaning products.

TECHNICAL SPECIFICATIONS

Chemical base:	Acrylic dispersion
Chemicals resistance:	Resistant to washing powders and detergents.
Colour:	White (Transparent)
Colour after curing/drying:	Transparent
Consistency:	Cream-like
Density approx.:	1,04 g/cm ³
Drying/Curing time approx.*:	5-10 minutes
Elasticity:	Good
Final bond strength after:	30 minutes
Flexible:	Yes
Minimum application temperature:	10 °C
Minimum temperature resistance:	-20 °C
Maximum temperature resistance:	90 °C
Moisture resistance:	Good
pH-value approx.:	4,5
Solid matter approx.:	45 %
Solvent free:	Yes
Viscosity:	Liquid
Viscosity approx.:	6000 mPa·s
Washable:	Yes
Water resistance:	Very good

* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

PACK SIZES

tube: 38ml on blistercard

STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.