

**UHU®**

# LOW MELT GLUE STICKS

## TRANSPARENT, ELASTIC, OVAL SHAPED



### PRODUCT DESCRIPTION

Transparent and elastic oval shaped low melt glue sticks for almost all materials, even suitable for use on polystyrene and other heat-sensitive materials. Their oval form prevents them from being mistakenly fitted into hot melt glue guns.

### FIELD OF APPLICATION

Suitable for metal, wood, glass, ceramic, leather, textiles, many plastics etc. Even glues heat-sensitive materials such as polystyrene and soft PVC quickly, cleanly and reliably. Ideal for handicraft, decorating, and repairing.

Not suitable for larger surfaces, Polyethylene (PE), Polypropylene (PP) and P.T.F.E. Do not use on supporting elements or objects permanently under tension.

### PROPERTIES

- Transparent and elastic
- Also suitable for use on heat-sensitive materials such as polystyrene, soft PVC, etc.
- Oval form, specially developed for UHU CREATIVE low melt glue guns
- Solvent- free

### PREPARATION

**Surface Requirements:** The areas to be glued must be dry and free of any dust or grease.

### APPLICATION

#### Directions for use:

Apply the glue quickly, and not too sparingly. Stick the two pieces together immediately. Always apply the glue to the harder material. Glue application: on flexible surfaces, apply the glue in thick lines, on hard surfaces, you can apply the glue in thick lines or in dots. The glue can be used to fill small holes and cracks.

**Stains/residue:** Cured adhesive residue can only be removed mechanically.

**Points of attention:** Do not use at temperatures below +5 °C. Never remove glue sticks from glue gun, this could damage the mechanism.

### TECHNICAL SPECIFICATIONS

Chemical base:	Ethylene vinylacetate copolymer
Colour:	White
Colour after curing/drying:	Translucent
Consistency:	Solid
Elasticity:	Good
Insulating:	Good
Melting temperature Minimum:	105
Melting temperature Maximum:	130 °C
Maximum temperature resistance:	75 °C
Open time approx.:	30 seconds
Solvent free:	Yes

### PACK SIZES

Available in: · 10 pieces · 15 pieces · 1000 pieces

### STORAGE CONDITIONS

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.