



THE ALL PURPOSE ADHESIVE

CRYSTAL-CLEAR SYNTHETIC RESIN ADHESIVE FOR A UNIVERSAL APPLICATION



PRODUCT DESCRIPTION

UHU All Purpose Adhesive, the proven liquid synthetic resin adhesive for fast and crystal-clear bonds. Suitable for universal applications at home, in the office, for modelling, at school, for crafts etc. Glues various materials rapidly and durably. Once applied, the glue remains temporarily adjustable and does not wrinkle paper.

FIELD OF APPLICATION

Universal - glues wood, wood based materials, plastics (ABS, hard and soft PVC, Plexiglas®, polystyrene, Resopal®), metal, glass, porcelain, ceramic, leather, rubber, felt, cork, fabrics, cardboard, paper, many plastics and much more. Not suitable for Styrofoam®, Polyethylene (PE) and Polypropylene (PP).

PROPERTIES

- Liquid
- Crystal-clear
- Fast drying
- Temporarily adjustable
- Does not wrinkle paper

PREPARATION

Working Conditions: Do not use at temperatures below +5 °C.

Surface Requirements: Materials to be glued must be clean, dry and free of dust and grease.

Preliminary Surface Treatment: When glueing plastics or metal, better results can be obtained if the parts to be stuck together are slightly roughened first.

APPLICATION

Directions for use:

Apply the adhesive thinly to one side of the assembly, press the parts together - that's it! For non-absorbent materials (e.g. ceramic, coated papers), apply to both sides of the assembly, leave to dry, re-apply and press the parts together.

Stains/residue: Remove wet glue stains immediately. Dried glue residue and glue stains in clothing can be removed with denatured alcohol.

Points of attention: Contains volatile, highly inflammable solvents. Appropriate precautions should therefore be taken during storage or when working with the adhesive.

TECHNICAL SPECIFICATIONS

| | |
|----------------------------------|--------------------------------|
| Chemical base: | Polyvinyl acetate |
| Colour: | Crystal clear |
| Consistency: | Liquid |
| Density approx.: | 0,98 g/cm ³ |
| Drying/Curing time approx.*: | 60-120 seconds |
| Filling capacity: | Good |
| Final bond strength: | 7 N/mm ² |
| Final bond strength after: | 24 hours |
| Flash point: | K1 (<21°C) |
| Minimum application temperature: | 10 °C |
| Maximum temperature resistance: | 70 °C |
| Moisture resistance: | Good |
| Solvent: | Mixture of esters and alcohols |
| Viscosity: | Medium viscosity |
| Viscosity approx.: | 4400 mPa·s |
| Water resistance: | Good |
| Water soluble: | No |

* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

PHYSIOLOGICAL PROPERTIES

The dried adhesive is inert, completely neutral and physiologically indifferent.

PACK SIZES

tube: 7ml, 20ml, 35ml, 45ml, 60ml, 125ml

STORAGE CONDITIONS

Store in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.